

276

# Insulation

Top Price Board 2 m<sup>2</sup>



Heat conductivity: X-trem-Insulation 0,020-0,035

**Extremely easy to work with**  
i.e. with a knife. The insulation will not tear, frazzle or leave any fibres

Insulation	Heat Conductivity (W/M x K)	Diffusion Resistance Measure	Price for 40 mm
<b>X-trem-Isolator</b>	<b>0,020-0,035</b>	<b>moisture proof</b>	<b>+ 4,0</b>
Polystyrol	0,025-0,040	20-300	0
Polyurethane	0,025-0,035	30-100	+ 3,0
Mineral fibrer	0,035-0,050	1	+ 0,0-2,5
Cork	0,045-0,055	10-20	+ 4,5-6,0



● **Extremely heat Insulating**  
Mountaineers use this for sleeping on the ice, thickness of the mat: 15 mm



● **Extremely light**  
and this fact save you a lot of fuel costs during your travel



# Reimo X-trem-Isolator ®

X-trem-Isolator This material does not absorb any moisture, is extremely flexible (360°), and fits perfectly to the vehicle body. It does not create noise, is resistant against high temperatures and solvents, biologically safe, protects from noise intrusion.

**Board size appr. 1 x 2 m**, Price per board (Shipment only via carrier)

Thickness 10 mm **50015**  
 Thickness 15 mm **50016**  
 Thickness 20 mm **50017**

for board thickness 10 - 20 mm shipment/packeging  
 1-4 boards  
 5-9 boards  
 10-20 boards Europalette.  
 ab 21 boards (max. 2m height)

Thickness 30 mm **50018**

for board thickness 30 mm shipment/packeging  
 1-3 boards  
 4-6 boards  
 7-10 boards Europalette.  
 ab 11boards (max. 2m height)

**Floor Insulation VW T2** (up to 7/90) size 1,56 x 1,56 m.

Thickness 15 mm **50005**

**Floor Insulation VW T4** (from 91) Size 1,53x2,37 m.

for floor board VW T4 short wheel-base), without recess for wheel arch and B-column, per board, thickness 15 mm **50006**

**Rolls** appr. 20 mm thickness. Price per meter

1,03 m wide **50019**

1,45 m wide **50022**

**Note: X-trem Isolation:** Colours and sizes of the mats may vary. The density of the mats may also vary which does not at all affect the quality of the material. Please check our product before using (sample). No warranty.

## Spezial Adhesive for X-trem-Isolator

- ① **Spray Adhesive**  
To affix small areas of X-trem Isolator onto metal, wood or plastic  
500 ml Spray Can. **50011**
- ② **Super-Spray Adhesive**  
Heat-resistant up to 90°C with imidiate glue effect. Affixes metal, wood or plastic. 500 ml **50013**
- ③ **One-Component Adhesive**  
Adhesive to affix large areas of X-trem Isolator. Application with brush or spatulal. 650 gr can **52715**
- ④ **3M Scotch Grip**  
High temperature adhesive to affix X-trem. We use this product at Reimo. May be sprayed. 1 l Can **50027**
- ⑤ **PU-Foam**  
To fill in difficult to reach hollow spaces. Note: Expands significantly in volume. FCKW-free. Effective volume 32 l **50010**

## ⑥ Sound-absorbing Insulation Mats

Reduce driving / engine noise. Mat size: 1000x500 mm.  
**Surface protected against:** no moisture can penetrate. **Insulating against:** Heat and cold. **Resistant against: Oil, water and petrol.**  
 Easy to work on with a knife. Self-adhesive foil on the back.

- Set I:** 2 mats 15 mm **50024**  
**Set II:** 3 mats 15 mm **50025**  
**Set III:** 4 mats 2 mm **50021**  
**Set IV:** 2 mats 22 mm (2/ 20 mm) **50023**



self-adhesive for quick mounting



⑥